

515nm~520nm 800mW 9-Pin Package Fiber Coupled Diode Laser With MM Fiber | Green LD Module
520nm| 700mW~800mW Output Power | 9-Pin Package | High Power Laser |Built-in TEC Cooling | Built-in PD
WSLX-520-800m-M-H9-T-PD **Wavespectrum Laser Group** **www.wavespectrum-laser.com**


PARAMETER	SYMBOL	VALUE	UNIT
MAX Reverse Current	I_r	80	mA
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-40 ~ +85	°C
Lead soldering temperature (5 sec.)	T_{is}	260	°C

Features: 520nm - Multi-mode Fiber - Built-in TEC Cooling - Built-in Photodiode - High Stability	
Applications: - Medical Laser Treatment - Others	

Specifications	WSLX-520-800m-M-H9-T-PD		
	Min.	Type	Max.
Center Wavelength@25°C	510nm	520nm	535nm
Spectral Width (FWHM)	----	2nm	----
Output Power	700mW	800mW	----
Recommend Operating Temperature	25 °C		
Threshold Current (Typ.)	----	0.2A	0.5A
Operating Current (Typ.)	----	1.6A	1.8A
Operating Voltage		5.0V	6.0V
TEC Max Current	6A		
TEC Max Voltage	9.8V		
Thermistor	10K		
Fiber Core	105um (50um, 200um Optional)		
Fiber Length	>80cm		
Connector Type	SMA905 / FC		
Package	9-Pin		



9-PIN HHL Package View



PIN	FUNCTION
1	TEC (-)
2	-
3	CASE
4	LD (+)
5	THERM
6	THERM
7	LD (-)
8	PD (P)
9	PD (N)
10	TEC (+)

Wavespectrum offer **Customized 520nm Fiber Coupled LD.**

- Customized Output Power
- Customized Fiber Core
- Dual-Wavelength or Tri-Wavelength Module Optional
(such as 2W@520nm+7W@808nm)

Contact us with info@wavespectrum-laser.com

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.



Wavespectrum Laser Group
www.wavespectrum-laser.com
sales@wavespectrum-laser.com

